技术参数表 | 型号: 770-101

锁定卡; 用于自由导线对接; 适用于手动操作; 黑色

https://www.wago.com/770-101



颜色: ■ 黑色

Locking system WINSTA® MIDI

Implement your installation project with ease: The locking system from the WINSTA® MIDI product line is the solution for error-free electrical installation. A comprehensive range of accessories rounds out the WINSTA® product line from WAGO. The WINSTA® MIDI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates exemplary electrification. Due to the built-in test slot, it is possible to check connections even when they are plugged in. This saves time, labor, and money.

WINSTA® MIDI solutions for your electrical installation – protected against mismating and maintenance-free

The WINSTA® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and consequently more efficient, even more reliable, and error-free. Using this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismating from WAGO makes the electrical installation of electrical components visibly easier.

- pre-assembled versions
- fast, secure installation

注意:

一般安全信息	**注意：请遵守安装和安全说明!** 1. Only to be used by a qualified electrician or by a person electrically instructed for the task (EIP per DIN VDE 0105-100). 2. Do not install while energized or under load. 3. Use only for its intended purpose. 4. Observe applicable national regulations, standards and directives. 5. Observe the technical specifications of the products. 6. Ensure correct polarity assignment. 7. Do not use damaged or contaminated components. 8. Observe conductor types, conductor cross-sections, strip lengths and cable diameters. 9. Insert conductors up to the stop. 10. Use only with locking lever and strain relief. 11. Use original accessories only. **本产品必须连同安装说明一同销售!**

连接数据

连接1

操作方式	手指按压键

机械参数

适用	适于自由摆放式连接；适于徒手操作

材料参数

注意事项（材料数据）	有关材料规范的信息请点击此处
颜色	黑色
绝缘材料（主壳体）	尼龙(PA 66)
符合UL94的阻燃等级	V0
火灾荷载	0.019 MJ
重量	0.6 g

环境要求

加工温度	-5 … +40 °C
连续工作温度	-35 … +85 °C
持续工作温度说明	绝缘部分适用温度 ≤ 105 C

商业数据

Product Group	20 (Winsta)
PU (SPU)	100 (25) 个
包装类型	盒
原产国	DE
GTIN	4017332660907
海关税则号	85389099990

产品分类

UNSPSC	39121702
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

环保产品合规性

RoHS 合规状态	Compliant,No Exemption

认证/证书

般認證

认证	标准	证书名称
VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808

下载

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-101

文档

Bid Text

770-101	19.02.2019	xml 2.62 KB
770-101	11.03.2015	doc 21.50 KB

CAD/CAE-Data

CAD data

2D/3D Models 770-101

CAE data

WSCAD Universe 770-101

ZUKEN Portal 770-101

安装说明

锁定系统



Locking lever, manually operated:
- Push on locking lever
- Pull the connectors apart